

U.S. Serial No. 09/784,885
Reply to Office Action Dated: 10/28/2003
Family Number: P1998J135A

Page 2 of 13

AMENDMENTS TO THE SPECIFICATION

Please add the following three new paragraphs before the last paragraph on page 10:

A preferred fuel has the following properties:

T₁₀, °F ≤ 140; T₅₀, °F > 215 ≤ 220; T₉₀, °F < 330 RVP, psi ≤ 7.0; S, ppmw ≤ 50; oxygen, wt% ≤ 3.5; aromatics, vol% of not more than 28; olefins, vol% ≤ 10; benzene, vol% < 1.0; paraffins, vol% ≤ 75; API° ≥ 59.

Another preferred fuel has the following properties:

T₁₀, °F ≤ 140; T₅₀, °F > 215 ≤ 220; T₉₀, °F < 330 RVP, psi ≤ 7.0; S, ppmw ≤ 50; oxygen, wt% ≤ 1.5-2.9; aromatics, vol% ≤ 35; olefins, vol% ≤ 10; benzene, vol% < 1.0; paraffins, vol% ≤ 75; API° ≥ 59.

Preferably, the fuels have a RVP psi of 6.6 to 6.9, more preferably a RVP psi of 6.6 maximum, a T₉₀ °F of 315-330, more preferably 315-325, a T₅₀ °F of 215 to 218, a sulfur content in ppmw of ≤ 35, preferably not more than 25, an oxygen content in wt% of ≤ 2, an aromatics content of not more than 28 vol%, more preferably 10 to 20 vol%, and a benzene content of not more than 0.80 vol%, preferably not more than 0.70 vol%.